

Pro Aquaseal™

Penetrating Sealer

Pro Aquaseal is a water-based penetrating sealer formulated to protect natural and quartz composite stone surfaces and ease maintenance of ceramic and porcelain tiles.

Uses

- ◆ To protect against household dirt and stains
- ◆ To provide water repellent and oil repellent protection
- ◆ For floors, walls, counters, showers and backsplashes
- ◆ For polished, vitrified, honed, brushed or textured surfaces
- ◆ On slate, marble and other calcareous stones, quartz composite stones, granite and natural stone, ceramic, porcelain and cement grout joints
- ◆ For residential, commercial and institutional applications
- ◆ For interior and exterior applications
- ◆ Contributes to LEED® objectives and requirements

Packaging

946 mL (1 U.S. qt) bottle; 4 L (1.05 U.S. gal) bottle

Limitations

- ◆ Do not use at temperatures below 10°C (50°F) or above 35°C (95°F).
- ◆ Do not use on plaster joints, wood parquet, vinyl flooring.
- ◆ Can be used on marbles and calcareous stones in showers or walls. In other cases, use Pro HS-Sealer for floor finishing (see the technical data sheet).
- ◆ Do not use for sealing epoxy joints, such as Pro Superpoxy 2, since they are already stain resistant, 100% solids (see data sheet for details).
- ◆ Do not use in extremely humid areas (public showers, saunas, pools)
- ◆ Adversely affected by abrasives and/or strong alkali cleaners

Surface Preparation

Surfaces must be clean and free of dust, oil, grease, paint, tar, wax, curing agent, primer, sealer, form release agent or any deleterious substance and debris which may prevent or reduce adhesion.

Mixing

No mixing required. Pro Aquaseal comes in a ready-to-use container.

Application

Note: Test on a small area to determine ease of application and desired results. Wearing of rubber gloves and safety glasses is recommended during application.

NEW OR NEVER SEALED GROUT:

Wait until curing time is over approx 7 to 14 days (see manufacturer's recommendation). Deep clean surface with Proma Pro Decap as per recommendation before sealing.

PREVIOUSLY SEALED GROUT:

Strip old sealer with appropriate Proma remover as per recommendation:

- To remove water base sealer: use Pro Decap
 - To remove solvent base sealer: use Pro Remover
1. Apply one thin coat evenly with a dry cloth, a sponge, a paint brush or a paint roller.
 2. Wait 15-20 minutes to allow the sealer to penetrate the surface.
 3. If sealer is totally absorbed in the tile, apply a second coat while the surface is still damp.
 4. Wait another 15-20 minutes to allow the sealer to penetrate.
 5. Wipe off excess sealer with a dry cloth or a paper towel.
 6. Let the surface dry 8 hours before using it.

Vertical applications: make sure there are no accumulations of sealer on the grout joints at the top of every tile to prevent excess sealer to slowly leek and create streaks on the surface of the tiles.

Drying Period

Dries within 1 to 3 hours. Reaction time 36 to 72 hours. Normal circulation or use generally after 72 hours.

Technical Data

Color.....	white translucent
Color Enhancement.....	low
Gloss.....	none
Odor:.....	faint
pH:.....	7.8
VOC Content:.....	15 g/100 mL

Approximate Coverage (based on 946 mL [1 U.S. qt.])

25 m² (250 ft²)

Varies depending on porosity and texture of surface, temperature, humidity and method of application.

Shelf life:

24 months if kept in its original unopened packaging and stored in a dry location. Protect from freezing.

Health and Safety:

ALWAYS KEEP AWAY FROM CHILDREN
Refer to the Material Safety Data Sheet (MSDS) for complete details.

Warranty

Proma warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. Proma's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

Contact Information

PROMA Adhesives Inc.

8500 Ernest-Cormier, Anjou, Quebec Canada H1J 1B4

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

