



PRO DECAP™

2. MANUFACTURER

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO DECAP is a degreasing cleaner for tiles, natural stones, quartz and grout joints, that deep-cleans most domestic stains; removes waxes, water-based acrylic and urethane sealers and finishes. PRO DECAP also removes pre-mixed acrylic and urethane grout residues as well as urethane construction glue residues on hardwood and urethane foam sealants.

Features

- ◆ Use on ceramic and porcelain tiles, natural stone and quartz
- ◆ Use on cementitious and epoxy grout
- ◆ Use on paving stones and concrete surfaces
- ◆ Use on vinyl, Luxurious Vinyl Tiles (LVT) and Vinyl Composition Tiles (VCT)
- ◆ Use on floors, walls, counters and backsplash
- ◆ Alkaline formula, non-corrosive
- ◆ No phosphates or ammonia
- ◆ Fast evaporation
- ◆ Low odor
- ◆ Removes heavy dirt and grease
- ◆ Removes ink and marker stains
- ◆ No VOC
- ◆ For interior and exterior institutional, commercial and residential applications
- ◆ Biodegradable. In conformity with OCDE 301 E rule
- ◆ Meets EcoLogo specifications Floor stripper CCD: 147B
- ◆ Meets EcoLogo specifications for Paint & Varnish Removers CCD:051
- ◆ Meets Long Term Removability Properties of Emulsion Floor Polishes test ASTM D1792-06
- ◆ Meets Cleaning Performance test ASTM D4488-95-A5

Packaging

946 mL (32 oz) bottle; 4 L (1.05 US gal) bottle

Limitations

- ◆ Works best at temperatures between 10°C (50°F) and 35°C (95°F).
- ◆ Do not use over MDF planks and boards.
- ◆ Do not use concentrated on surfaces with a sealer.
- ◆ May attack pre-mixed acrylic or urethane grouts.
- ◆ May damage porous slate colors.



4. TECHNICAL DATA

Applicable Standards

For Additional Information, please refer to the most recent TCNA handbook for ceramic tile installation or the TTMAC Specification Guide 09 30 00 Tile Installation Manual, or visit our website at www.proma.ca.

PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)	
VOC content	0 g/100 ml
Color	Clear amber
Odor	Low odor
Approximate coverage	Varies with the cleaning concentration required and the surface condition.
Shelf life	24 months if kept in its original unopened packaging and stored in a dry location. Protect from freezing.

5. INSTALLATION

Application and Mixing

Note: Grout must be fully cured at least 28 days old prior to use. Test on a small area to determine ease of application and desired results. Wear gloves and safety glasses when using this product, and protect neighboring areas against unexpected contact with product to avoid possible damage.

Deep Cleaning – Ceramic, Porcelain and Unsealed Natural Stones

1. Pour undiluted cleaner on the surface and spread with a white or black nylon scuff pad or a hard bristle nylon brush. Let the solution work 3 to 5 minutes. Work in sections – do not allow stripping solution to dry on the surface. Use white scuff pads on marbles, calcareous stones and soft surfaces sensitive to abrasion.
2. Add an equivalent amount of warm to hot water on the surface and scrub. Let the solution work another 3 to 5 minutes while scrubbing.
3. Remove the solution with a mop or preferably with a wet vacuum, rinse thoroughly and pick up.

Deep Cleaning – Surface Sealed with an Acrylic Finish or Sealer

CAUTION: Product when used full strength may remove the sealer

1. Dilute cleaner using 1 part cleaner with 3 - 4 parts of warm water. Increase concentration if required.
2. Pour cleaning solution onto the surface and spread with a white or black nylon scuff pad or a hard bristle nylon brush. Use white scuff pads on marbles, calcareous stones and soft surfaces sensitive to abrasion.
3. Let the solution work 3 to 5 minutes. Work in sections – do not allow stripping solution dry on the surface. For large areas, use a low-speed buffing machine with appropriate scouring pad. Remove the solution preferably with a wet vacuum, rinse thoroughly with warm clear water and pick up.
4. Let dry 24 hours before applying another sealer of finish.

Wax and Water Based Finish and Sealer Removal

1. Mix 1 part of cleaner with 1 to 2 parts of warm water. Increase concentration if needed. To remove a urethane water-based sealer, use without dilution.
2. Using a mop, spread generously and let work 5 to 10 minutes while scrubbing with an appropriate nylon scuff pad. Work in sections – do not allow stripping solution dry on the surface. For large areas, use a low-speed buffing machine with appropriate scouring pad. Remove the solution preferably with a wet vacuum, rinse thoroughly with warm clear water and pick up.
3. Let dry 24 hours before applying another sealer of finish.

Pre-Mixed Grout Residue Removal

1. Pour undiluted cleaner on the tiles and spread with a nylon scuff pad. Use a black scuff pad on ceramic, porcelain, vinyl - LVT and natural stone surfaces other than marbles and calcareous stones. For those, use only a white scuff pad so to no damage the finish of the stone.
2. Let the solution work 3 to 5 minutes. Work in sections – do not allow stripping solution dry on the surface. When the residues start to be released, add an equivalent amount of warm water on the surface and scrub the surface until the surface is free from any residues. Avoid scrubbing the joints as much as possible to avoid stripping them.
3. Remove the solution with a mop or preferably with a wet vacuum, rinse thoroughly and pick up.

Urethane Construction Glue Removal

1. Pour undiluted on the glue residues and scrub lightly with a white nylon scuff pad.
2. Allow remover to soften and release the glue residues for approx. 5-10 minutes.
3. Wipe with a damp cloth and let dry.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for complete details.

6. AVAILABILITY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free: 1.866.51.PROMA (77662)**.

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. MAINTENANCE

Product requires no special maintenance.

9. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA (77662)**.

10. FILING SYSTEM

Additional information is available upon request, or by visiting **www.proma.ca**.

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

© 2017 PROMA Adhesives, Inc.