



PRO REMOVER™ II

2. MANUFACTURER

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO REMOVER II is a biodegradable organic cleaner designed to safely remove PRO GROUT XTREME™ epoxy grout residue from tile and stone surfaces.

Features

- ♦ Use to remove PRO GROUT XTREME™ epoxy grout residue
- ♦ Use on ceramic, porcelain and most natural stone and quartz surfaces
- ♦ Use on countertops, floors and walls
- ♦ Works on all epoxy grouts
- ♦ Safe on concrete
- ♦ Viscous formula for a long lasting action and vertical application
- ♦ Slow evaporation for a long term action
- ♦ Low odor
- ♦ Safe on metals
- ♦ No VOC
- ♦ For interior and exterior institutional, commercial and residential applications
- ♦ Biodegradable. In conformity with OCDE 301 E rule
- ♦ Meets EcoLogo specifications Floor stripper CCD: 147B
- ♦ Meets EcoLogo specifications for Paint & Varnish Removers CCD:051
- ♦ Meets Chemical Remover for Organic Coating test ASTM D6189-97

Packaging

946 mL (32 oz) bottle; 4 L (1.05 US gal) bottle

Limitations

- ♦ Works best at temperatures between 10°C (50°F) and 35°C (95°F).
- ♦ Do not use over MDF planks and boards.
- ♦ May affect sealer in place.



4. TECHNICAL DATA

Applicable Standards

For Additional Information, please refer to the most recent TCNA handbook for ceramic tile installation or the TTMAC Specification Guide 09 30 00 Tile Installation Manual, or visit our website at www.proma.ca.

WORKING PROPERTIES (@23° C [73° F] and 50% RH)

Working time	
24 – 48 hours after grouting	15 minutes - 3 hours
72 hours or more after grouting	30 minutes - 8 hours

PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)

VOC content	0 g/100 ml
Color	Amber
Odor	Low odor
Approximate coverage	Varies with the surface condition.
Shelf life	
24 months if kept in its original unopened packaging and stored in a dry location. Protect from freezing.	

5. INSTALLATION

Mixing

No mixing required. PRO REMOVER II comes in a ready-to-use container.

Working Time

Epoxy Grout Residues:

24 – 48 hours after grouting: 15 minutes - 3 hours

72 hours or more after grouting: 30 minutes - 8 hours

Note: Exposure time may vary with the thickness of the grout residues, as well as the room temperature and if the surface is vertical or horizontal.

Application

Note: Test on a small area to determine ease of application and desired results. Wear gloves and safety glasses when using this product, and protect neighboring areas against unexpected contact with product to avoid possible damage.

1. Pour remover on to the surface and spread with a nylon scuff pad. Use a black scuff pad on ceramic, porcelain, vinyl - LVT and natural stone surfaces other than marbles and calcareous stones. Use a white scuff pad on marbles, calcareous stones and soft surfaces sensitive to abrasion.
2. Let the solution work 3 to 5 minutes. Work in sections – do not allow the stripping solution to dry on the surface.
3. When the residues start to be released, add an equivalent amount of warm to hot water on the surface and scrub the surface until the surface is free from any residues. Avoid scrubbing the joints as much as possible to avoid stripping them.
4. Remove the solution with a mop or preferably with a wet vacuum, rinse thoroughly and pick up.





Application Issues

Grout Residue Still Visible on Tiles After Cleanup

Grout residue still visible on tiles after cleanup usually occurs when rinsing was not properly done or when exposure time or working time has not been sufficient.

Main causes

- ♦ Not enough PRO REMOVER II is used on the surface of the tiles to allow to work properly.
- ♦ Not allowing enough time for PRO REMOVER II to work properly.
- ♦ Not adequately rinsing the surface of the tiles with the appropriate scuff pad to remove all traces of grout and PRO REMOVER II residues.

Corrective measures

- ♦ Dry scrub the surface with a black nylon scuff pad and rinse with a 25% concentrated solution of PRO DECAP™ (see respective data sheet for details). Wipe surface with a white paper towel to make sure there is no residue left on the surface. Use a white scuff pad on marbles, calcareous stones and soft surfaces sensitive to abrasion.
- ♦ Go through the PRO REMOVER II stripping procedure again making sure the quantity of remover used is enough, the time of action is sufficient and the rinsing procedure is done properly.

Health and Safety

Refer to the Safety Data Sheet (SDS) for complete details.

6. AVAILABILITY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free: 1.866.51.PROMA (77662)**.

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. MAINTENANCE

Product requires no special maintenance.

9. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA (77662)**.

10. FILING SYSTEM

Additional information is available upon request, or by visiting www.proma.ca.

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

© 2017 PROMA Adhesives, Inc.

