



PRO SHOWER™

2. MANUFACTURER

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO SHOWER is designed for routine cleaning of showers. It incorporates a surface treatment to avoid water stains and accumulation of soap and calcareous residues. It eliminates the need to use a squeegee and is ideal for glass, ceramic, granite and Quartz surfaces. Not to be used on marble and calcareous stones.

Features

- ♦ Excellent for routine shower cleaning and hydrophilic treatment
- ♦ Acidic formula – pH: 3.5-4
- ♦ No phosphates or ammonia
- ♦ Dries quickly
- ♦ Leaves no streaks
- ♦ No VOC
- ♦ Meets Cleaning Performance test ASTM D4488-95-A5
- ♦ Biodegradable. In conformity with OCDE 301 E rule
- ♦ For interior residential, commercial and institutional use

Packaging

Ready-to-Use Formula:

700 mL (23.6 oz) bottle; 2 L (2.1 US qt) bottle

Maintenance kit for Showers – Ceramic, Granite, Quartz & Glass:

700 mL (23.6 oz) bottle; 500 mL (16.0 oz) bottle PRO NET™

Recommended Surfaces

- ♦ Glass surfaces
- ♦ Ceramic and porcelain tiles
- ♦ Granite
- ♦ Quartz
- ♦ Chrome
- ♦ Stainless steel
- ♦ Glass tiles
- ♦ Shower walls and glass

Limitations

- ♦ Best performance at temperature between 15°C (60°F) and 30°C (86°F).
- ♦ Will etch the surface of marble, travertine, cobblestone, limestone and calcareous stones.
- ♦ May damage the sealer on tiles.

4. TECHNICAL DATA

Applicable Standards

For Additional Information, please refer to the most recent TCNA handbook for ceramic tile installation or the TTMAC Specification Guide 09 30 00 Tile Installation Manual, or visit our website at www.proma.ca.



PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)	
VOC content	0 g/L
pH	3.5 - 4
Odor	Faint
Approximate coverage *	
700 mL (23.6 oz) bottle	27.9 m ² (300 ft ²)
Shelf life	
24 months if kept in its original unopened packaging and stored in a dry location with temperatures between 10°C (50°F) to 30°C (86°F). Protect from freezing.	
*Varies with the method of application and the surface condition.	

5. INSTALLATION

Prevention Measures

PERSONAL SAFETY

- ♦ Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.
- ♦ Please follow safety guidelines outlined in the "CAUTION" section indicated on the bottle (see hereunder).

NEIGHBORING AREA PROTECTION

- ♦ Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement.

PREREQUISITE CONDITIONS

- ♦ Surface temperature should be between 15 and 30°C (60 and 85°F). Ideal temperature for best results.
- ♦ Test first on a small and adequate surface, to assess results.

First time user, without preliminary testing.

- ♦ Never use the product for the first time on a large area without preliminary testing.
- ♦ Usage of the product on a sensitive material could alter irreversibly the material that would only be restored by its replacement.

Using the product on a new surface or on an unknown surface, without preliminary testing.

- ♦ Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, presence of an incompatible substance that could be irreversibly damaged or altered or give unexpected end results that would only be restored by its replacement.
- ♦ More so, since the product is acid based, it can etch on contact any calcareous type surface such as: marble, cobblestone, travertine and other calcareous stones. Some of those stones can be confused with some ceramic or porcelain tiles that imitate them extremely well. But the reaction with the cleaner will be very harmful in the case of calcareous natural stones.

Methods of Application

Surface preparation first-time usage

- ♦ Surface should be clean, dry and free of any soap residues and mildew. If needed, deep clean the shower with PRO NET II. Follow the instructions on the label or on the Technical Data Sheet for the level of dilution required. Rinse thoroughly and let dry before using PRO SHOWER.

Cleaning with the ready-to-use formula in a 700 mL (23.6 oz) spray gun bottle

- ♦ Spray the cleaner on the surface straight from the bottle and spread out on all areas and/or to remove light dirt and soil with a white nylon scuff pad. Rinse with the shower head or wipe dry with a white paper towel. Allow 3 hours before using the shower.
- ♦ Afterwards, routine cleaning should be performed only with PRO SHOWER.

Application Issues

Whitish residue on the treated surface after drying

A whitish film may appear on the walls and glass after you cleaned the shower with PRO SHOWER.

Main causes

- ♦ Surface was not well rinsed, leaving excess residues of the hydrophilic treatment
OR
- ♦ Surface was not wiped dry with a white paper towel, leaving excess residues of the hydrophilic treatment

Corrective measures

- ♦ Rinse the surface thoroughly with hot water and scrub with a white or black nylon scuff pad.
- ♦ Please note that with time, the hydrophilic treatment excess residues will fade away and disappear after a number of showers.

Disposal

Do not dispose of excess cleaner into sewers; instead send to an appropriate recycling center.

Health and Safety

Refer to the Safety Data Sheet (SDS) for complete details.

6. AVAILABILITY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free: 1.866.51.PROMA (77662)**.

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. MAINTENANCE

Product requires no special maintenance.

9. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA (77662)**.

10. FILING SYSTEM

Additional information is available upon request, or by visiting www.proma.ca.

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

© 2017 PROMA Adhesives, Inc.