



PRO STAIN CLEANER™



2. MANUFACTURER

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO STAIN CLEANER is an oil and grease stain remover (poultice-like) for stone, concrete and paving stone.

Features

- ♦ Alkaline formula
- ♦ Won't etch marble and calcareous stones
- ♦ Safe for metals and glass
- ♦ Non-corrosive
- ♦ Slow evaporation for extended applications
- ♦ Faint odor
- ♦ No VOC
- ♦ Biodegradable. In conformity with OCDE 301 E rule
- ♦ Meets Cleaning Performance test ASTM D4488-95-A5
- ♦ For interior and exterior residential, commercial and institutional use

Packaging

450 gr bottle; 946 mL (32 oz) bottle; 4 L (1.05 US gal) bottle

Recommended Surfaces

- ♦ Natural stones
- ♦ Terrazzo
- ♦ Concrete
- ♦ Paving stone
- ♦ Asphalt

Limitations

- ♦ Best performance at temperature between 15°C (60°F) and 30°C (86°F).

4. TECHNICAL DATA

Applicable Standards

For Additional Information, please refer to the most recent TCNA handbook for ceramic tile installation or the TTMAC Specification Guide 09 30 00 Tile Installation Manual, or visit our website at www.proma.ca.

PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)	
VOC content	0 g/L
pH	9 - 10
Odor	Faint
Approximate coverage	Varies with the chemical composition of the stains as well as the surface condition.
450 gr	0.1 m ² (1 ft ²)
4 L (1.05 US gal)	2.5 m ² (25 ft ²)
Shelf life	
24 months if kept in its original unopened packaging and stored in a dry location with temperatures between 10°C (50°F) to 30°C (86°F). Protect from freezing.	

5. USAGE

Prevention Measures

PERSONAL SAFETY

- ♦ Wearing of gloves, safety glasses and appropriate clothing to prevent skin contact when using the product is always recommended.
- ♦ Please follow safety guidelines outlined in the "CAUTION" section indicated on the bottle (see hereunder).

NEIGHBORING AREA PROTECTION

- ♦ Always protect the neighboring working area against unexpected contact with the product to avoid irreversible damage or alterations that could only be restored by its replacement.

PREREQUISITE CONDITIONS

- ♦ Surface temperature should be between 15 and 30°C (60 and 86°F). Ideal temperature for best results.
- ♦ Test first on a small and adequate surface, to assess results.

First time user, without preliminary testing.

- ♦ Never use the product for the first time on a large area without preliminary testing.
- ♦ Usage of the product on a sensitive material could alter irreversibly the material that would only be restored by its replacement.

Using the product on a new surface or on an unknown surface, without preliminary testing.

- ♦ Even if you have used the product in the past, because covering manufacturers do modify occasionally the composition of their products, there could be, without your knowledge, addition of an incompatible substance that could be irreversibly damaged or altered and only be restored by its replacement.
- ♦ More so, even if the product is lightly alkaline, it could damage the finish or the protection of certain materials. Some acrylics (bathtubs, showers, sinks) are sensitive to alkaline cleaning products when used with the scrubbing action of nylon scuff pads.



- ◆ Finally, since 2016 we note that some polished Quartz products, Quartzite surfaces and flamed granites are very sensitive to alkaline products. Application of a wax or an acrylic finish by the manufacturers seems to be at the origin of the problem.

Methods of Application

1. Pour cleansing cream and cover the stain entirely, then let dry (average drying time is 8 hours).
2. When dry, the product will change to a hard powder. Sweep the surface with a hard bristle brush.
3. Repeat if necessary.

Disposal

Do not dispose of excess remover into sewers; instead send to an appropriate recycling center.

Health and Safety

Refer to the Safety Data Sheet (SDS) for complete details.

6. AVAILABILITY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free: 1.866.51.PROMA (77662)**.

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA (77662)**.

9. FILING SYSTEM

Additional information is available upon request, or by visiting www.proma.ca.

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3
Tel.: 514.852.8585
Fax: 514.852.8225
Toll-free: 1 866.51.PROMA (77662)
Email: info@proma.ca

© 2018 PROMA Adhesives, Inc.

