

Intertek does hereby certify that an independent assessment has been conducted on behalf of

PROMA ADHESIVES INC.

Certificate Number: CA-88912-2022c Certification valid until: 05 July 2023

Applicant Address: 9801 Parkway

Anjou, QC H1J 1B4 Canada

Product Category: Building Products

Product Details: See Appendix

Conformance Criteria: California Department of Public Health (CDPH) Standard Method v1.2: Private Office, School Classroom, Single Family Residence.

Issuing Office Name & Address: Intertek Testing Services NA, Inc.

4700 Broadmoor Ave SE, Suite 200

Kentwood, MI 49512 USA Ph: +1-616-656-7401

Jesse Ondersma Certification Officer 18 August 2022

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Certificate are relevant only to the sample tested/inspected. This Certificate by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Certificate Appendix

PROMA ADHESIVES INC.

Certificate Number: CA-88912-2022c

| Product Category | Mortar and Grout |
|-------------------------|---|
| Model Name(s) | Polymer Modified Mortars: PRO HPX™ (GREY AND WHITE), PRO P-151™ (GREY AND WHITE), PRO P-151™ SF (GREY AND WHITE), PRO SUPERLITE MORTAR™, PRO FLEX® SELECT (GREY AND WHITE), PRO QUICK™ SET (GREY AND WHITE), PRO FLEX® SET (GREY) High Performance Grout: PRO GROUT™ MAX (LIGHT AND DARK) |
| Product Restrictions | None |
| TVOC Range* | 0.5 mg/m ³ or less |

^{*}TVOC range stated is based on the most stringent modeling scenario as listed in the Conformance Criteria on page 1.