




SURFACE PREPARATION - SELF LEVELLING UNDERLAYMENTS

Products designed to correct, level and smooth substrates.

- PRO LIQUID FINISH™ RS
- PRO PLAN™
- PRO PLAN™ CG
- PRO PLAN™ CG LIGHT ECO
- PRO FLOWLEVEL™ 40
- PRO FLOWLEVEL™ 40 LIGHT
- PRO FLOWLEVEL™ FIBER REINFORCED

VALIDATED ECO-DECLARATION

PRODUCT SPECIFICATIONS	ENVIRONMENTAL IMPACTS	TECHNICAL PERFORMANCES
References Pro Liquid Finish™ RS, Pro Plan™ CG, Pro Plan™ CG Light ECO, Pro Flowlevel™ 40, Pro Flowlevel™ 40 Light and Pro Flowlevel™ fiber reinforced.	Life Cycle Assessment -	Performance tests ANSI A118.16 ¹ ¹ : excludes Pro Liquide Finish™ RS and Pro Flowlevel™ fiber reinforced
Final manufacturing location Anjou, QC H1J 1P3 CANADA	Reference service life -	MANUFACTURER'S ENVIRONMENTAL MANAGEMENT
Composition Binder, filler, polymer, rheology modifier, retarder and other additives.	Product's carbon footprint -	ISO 14001 Certification -
ATTRIBUTES	Environmental Product Declaration EPD, Type III ISO 14025:2006 -	Extended Product Responsibility (Take Back Program) -
Recycled content Pre-consumer: 0.0% - 45.0% Post-consumer: 0.0% - 35.0%	INGREDIENTS AND EMISSIONS	Corporate Sustainability Report (CSR: GRI, ISO 26000, BNQ 21000 or others) -
Sourcing of raw materials Data collection from suppliers has been conducted for the products components aligned with each specific environmental analysis.	Declaration of chemical ingredients 1 000 ppm	CERTIFICATION(S) & CONFORMITIES
Certified Wood -	Type of declaration HPD® version 2.3 Health Product Declaration® In renewal	
Rapidly renewable materials -	Emissions test Complies with CDPH SM v1.2 ¹ Total VOC range: 0.5 mg/m ³ or less ¹ : excludes Pro Flowlevel™ 40, Pro Flowlevel™ 40 Light and Pro Flowlevel™ fiber reinforced.	Excludes Pro Flowlevel™ 40, Pro Flowlevel™ 40 Light and Pro Flowlevel™ fiber reinforced.
Biobased materials -	VOC 0 g/L	
	Formaldehyde -	
	Others -	

PROMA is a leading Canadian manufacturer of high-quality professional materials for the installation of flooring, which includes products for proper surface preparation; installation materials for tile, stone, and floor coverings; grout products; cleaners, and sealers.



ENVIRONMENTAL DATA SHEET



SURFACE PREPARATION - SELF LEVELLING UNDERLAYMENTS

PRODUCT CONTRIBUTION SUMMARY

LEED® v4 requirements for Building Design + Construction (BD+C)

New Construction, Core and Shell, Schools, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

LEED® v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

MATERIALS AND RESOURCES		PRODUCT CONTRIBUTIONS																					
MR	Building Product Disclosure and Optimization – Sourcing of Raw Materials Option 2: Leadership extraction practices (1 point) Requirements - Use products that meet at least one of the responsible extraction criteria: Recycled content, Wood products Certification, Bio-based materials, Extended producer responsibility.	Contribute	ATTRIBUTES Recycled content																				
			<table border="1"> <thead> <tr> <th></th> <th>Pre-consumer</th> <th>Post-consumer</th> </tr> </thead> <tbody> <tr> <td>Pro Liquid Finish™ RS</td> <td>9.0% - 27.0%</td> <td>0%</td> </tr> <tr> <td>Pro Plan™ CG</td> <td>18.0% - 36.0%</td> <td>0%</td> </tr> <tr> <td>Pro Plan™ CG Light ECO</td> <td>27.0% - 45.0%</td> <td>15.0% - 35.0%</td> </tr> <tr> <td>Pro Flowlevel™ 40</td> <td>0%</td> <td>0%</td> </tr> <tr> <td>Pro Flowlevel™ 40 Light</td> <td>0%</td> <td>10.0% - 20.0%</td> </tr> <tr> <td>Pro Flowlevel™ fiber reinforced</td> <td>0.1% - 0.5%</td> <td>0%</td> </tr> </tbody> </table>		Pre-consumer	Post-consumer	Pro Liquid Finish™ RS	9.0% - 27.0%	0%	Pro Plan™ CG	18.0% - 36.0%	0%	Pro Plan™ CG Light ECO	27.0% - 45.0%	15.0% - 35.0%	Pro Flowlevel™ 40	0%	0%	Pro Flowlevel™ 40 Light	0%	10.0% - 20.0%	Pro Flowlevel™ fiber reinforced	0.1% - 0.5%
	Pre-consumer	Post-consumer																					
Pro Liquid Finish™ RS	9.0% - 27.0%	0%																					
Pro Plan™ CG	18.0% - 36.0%	0%																					
Pro Plan™ CG Light ECO	27.0% - 45.0%	15.0% - 35.0%																					
Pro Flowlevel™ 40	0%	0%																					
Pro Flowlevel™ 40 Light	0%	10.0% - 20.0%																					
Pro Flowlevel™ fiber reinforced	0.1% - 0.5%	0%																					
MR	Building Product Disclosure and Optimization – Material Ingredients Option 1: Material ingredients reporting (1 point) The product contributes to this credit due to the availability of a Health Product Declaration® and is valued as 1 whole product out of the 20 needed for the purposes of credit achievement calculation.	Contribute	INGREDIENTS AND EMISSIONS HPD® version 2.3 Health Product Declaration® In renewal																				
EQ	Low-Emitting Materials Option 1: Product category calculation (1-3 points) Number of points is dependent on the LEED® rating system and the number of compliant categories. For the Interior Adhesives and Sealants Applied on Site category, at least 90% of adhesives and sealants, by volume, must satisfy the General Emissions Evaluation. Also, 100% of adhesives and sealants wet-applied on site must satisfy the VOC content requirements for wet applied products.	Contribute	INGREDIENTS AND EMISSIONS The products were tested and determined compliant in accordance with California Department of Public Health (CDPH) Standard Method (CDPH) v1.2-2017 for Private Office, School Classroom and Single Family Residence scenarios, except for Pro Flowlevel™ 40, Pro Flowlevel™ 40 Light and Pro Flowlevel™ fiber reinforced. AND The products conform to SCAQMD Rule 1168, July 1, 2005 or the Canadian VOC Concentration Limits for Architectural Coatings.																				
			PRODUCT CONTRIBUTIONS																				

It is important to consider that the total amount of possible points reflects the number of achievable points in each credit category. The product itself cannot achieve this score, as defined above, but is considered as a beneficial element in order to achieve LEED® credits.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and omissions relative to the collection, compilation and/or interpretation of data.

Validated Eco-Declaration:
VED22-1002-03
 Period of validity:
2026/05 to 2027/04
 ©Copyright 2016 Vertima inc.

