Safety data sheet for safe handling

of the product

Date of Issue: July 2013



Product name:

PRO COLOR SEAL

1. PRODUCT IDENTIF	ICATION
--------------------	---------

PHYSICAL PROPERTIES

Product information: Siliconized acrylic latex-based

colored caulking compound

Manufacturer:

PROMA Adhesives Inc.

Telephone: 514-852-8585

8500 Ernest-Cormier, Anjou Quebec, Canada H1J 1B4

EMERGENCY - CANUTEC (24 HOURS) 613-996-6666 Physical state Thick colored paste Odor Light ammonia odor PH (in water) N/A Melting point N/A Boiling point N/A Vapor pressure (mm Hg) N/A Density (water =1) 1,4 Vapor density (air = 1) N/A

Evaporation rate <1 (Butylacetate=1)

Water solubility N/A

2. **COMPOSITION**

Cas no. Ingredients % TIME WEIGHT AVERAGE **EXPOSURE VALUE (TWAEV)**

Breathing Dust Total Dust

64742-88-7 Solvent naphta aliphatic 0-1 Titanium dioxide 0-413463-67-7 10 mg/m³

FIRE AND EXPLOSION DATA

REACTIVITY DATA 5.

Flammability: Nonflammable. Stability: Stable

Hazardous polymerization: None

Incompatibility with other substances: N/A

N/A Flash point:

Extinguishing media: Pulverized water, foam,

carbon dioxide, chemical powder

None. A self-contained

breathing apparatus should

be used by the fire-fighters.

Risk of explosion: N/A

Sensitivity to static

Special procedures

to fight against fire:

discharge: N/A

Combustion products: Carbon monoxide

Carbon dioxide

If yes, which ones?

Hazardous products of decomposition:

Carbon monoxide

Carbon dioxide

PRO COLOR SEAL

Skin contact:

Effects of acute exposure:

6. TOXICOLOGICAL PROPERTIES

PREVENTIVE MEASURES

Route of entry: Inhalation, ingestion,

eye and skin contact

Ventilation: Use in well-ventilated area.

Skin protection: Wear protective gloves,

shoes and clothing to avoid skin contact.

Inhalation: May cause nose, throat and

respiratory system irritation. Respir

Respiratory No mask necessary for **protection:** normal handling.

Ingestion: Toxic. May cause irritation

to the intestinal tract.

Eye protection: Wear safety glasses.

May cause dryness, redness and **Leak/spill:** Wear necessary protective

equipment.

Place in closed containers

for disposal.

Eye contact: May cause irritation and eye

surface damage.

mild irritation.

Effects of chronic I.A.R.C. has concluded there is

exposure: sufficient evidence that inhaled crystalline silica in quartz form from

occupational sources is a carcinogen

for humans.

Waste disposal: Do not dump in sewer or

water pipes.

Dispose in accordance with

local regulations.

Storage: Avoid extreme temperatures.

Protect from freezing.

8. FIRST AID MEASURES

In case of ingestion: Do not induce vomiting.

Consult a physician.

In case of inhalation: Move the victim to fresh air.

Contact a physician if necessary.

In case of skin contact: Wash skin with soap and water.

Remove contaminated clothing.

Consult a physician if irritation persists.

In case of eye contact: Flush eyes with plenty of water, lifting

upper and lower eyelids.

Consult a physician if irritation persists.