

PRO BLOCK MMS ECO PART B

1. Identification

Product identifier: Other means of identification:	PRO BLOCK MMS ECO PART B
Recommended use:	MOISTURE MITIGATION MEMBRANE
Restriction on use:	Use only for indoor applications
Supplier Name:	ADHESIFS PROMA INC. 9801 boul. Parkway Anjou, Québec Canada, H1J 1P3
Telephone:	514 852-8585
Emergency tel. number:	1 866 517-7662
Available hours:	7h30 - 16h00 Monday to Friday

2. Hazard identification

Signal word:

DANGER

Product classification:



Skin corrosion - Category 1C. Skin corrosion - Category 1. Serious eye damage - Category 1. Health hazards not otherwise classified - Category 1 Corrosive. Corrosive to metals - Category 1.

Respiratory sensitization - Category 1. Specific target organ toxicity - repeated exposure - Category 2.

Skin sensitization - Category 1. Skin sensitization - Category 1A. Skin sensitization - Category 1B.

Hazard statement(s):

- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H374 Causes serious injury to the respiratory tract.
- H290 May be corrosive to metals.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H373 May cause damage to organs (lungs, kidneys) through prolonged or repeated exposure.
- H317 May cause an allergic skin reaction.

Precautionary statement(s)

Prevention: Keep only in original packaging. Do not breathe mist, vapors and spray. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection. In case of inadequate ventilation, wear respiratory protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a doctor. Wash contaminated clothing before reuse. Absorb spillage to prevent material-damage. IF ON SKIN: Wash with plenty of water. If skin irritation or a rash occurs: Get medical advice.







PRO BLOCK MMS ECO PART B

Take off contaminated clothing and wash it before reuse. If experiencing respiratory symptoms: Call a POISON CENTER or a doctor. Get medical advice if you feel unwell.

Storage: Store locked up. Store in a corrosive resistant container with a resistant inner liner.

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: Poison by intraperitoneal route.

See toxicological information, section 11

3. Composition/ Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	9046-10-0	Polypropylene glycol diamine	10.00 - 30.00 *
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	10.00 - 30.00 *
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	5.00 - 10.00 *
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	0.10 - 1.00 *
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	0.10 - 1.00 *

* The actual concentration range is withheld as a trade secret.

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting unless instructed by medical personnel.

Symptoms: This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death. The worker may develop skin hypersensitivity as well as allergic or asthma symptoms or breathing difficulties if inhaled.

Effects (acute or delayed): If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. This product is a respiratory and skin sensitizer. May cause photosensitization. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. High concentration exposure can lead to severe lesions and ulcerations of the esophageal mucosa and gastrointestinal tract. May cause lung, liver and kidney damage. Fever.



PRO BLOCK MMS ECO PART B

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: No specific hazard.

Hazardous combustion products: Ammonia. Carbon monoxide and dioxide. Nitrogen oxides.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Oxidizers. Strong acids and bases as well as strong oxidizing agent.



Kalium Solutions inc. All Rights Reserved.



PRO BLOCK MMS ECO PART B

8. Exposure Controls/ Personal protection

Control parameters:

Occupational exposure limit values:

Alberta

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute o exposure li	•	Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	10	25	Not listed	Not listed	Not listed	Not listed
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	1	4.2	Not listed	Not listed	Not listed	Not listed

British-Columbia

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		•		Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	10	Not listed	Not listed	Not listed	Not listed	Not listed
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	1	Not listed	Not listed	Not listed	Not listed	Not listed

Ontario

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)				Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed





PRO BLOCK MMS ECO PART B

Quebec

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute o exposure li	•	Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	10	25	Not listed	Not listed	Not listed	Not listed
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	1	4.2	Not listed	Not listed	Not listed	Not listed

Saskatchewan

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)				Ceiling ccupational exposure limit	
			ppm	mg/m ³	ppm	mg/m³	ppm	mg/m ³
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	10	Not listed	15	Not listed	Not listed	Not listed
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	1	Not listed	2	Not listed	Not listed	Not listed

United States

No	CAS No :	Common name and synonyms	IDLH	Re	egulatory	Limits	Recommer	ded Limits
			NIOSH	OSHA	OSHA PEL Cal OS		NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	2458	10	25	10 ppm	10 ppm	10 ppm
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

IDLH: Immediately Dangerous to Life or Health Concentrations NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration





PRO BLOCK MMS ECO PART B

PEL: Permissible Exposure Limits California / OSHA: California Division of Occupational Safety and Health REL: Recommended Exposure Limits ACGIH ®: American Conference of Governmental Industrial Hygienists TLV ®: Threshold Limit Values

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES. Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Liquid Colour: Yellow Odour: Amine-like Melting/Freezing point: Not available Initial boiling point/boiling range: > 117 °C (242.6 °F) Flammability: Not available Lower flammable/explosive limit: Not available Upper flammable/explosive limit: Not available Flash point: Not available Auto-ignition temperature: Not available Decomposition temperature: Not available pH: Not available Kinematic viscosity: Not available Solubility (in water): Not applicable Partition coefficient - n-octanol/water (Log Kow): Not available Vapour pressure: Not available Density and relative density: Not available Relative vapour density: Not applicable Particle characteristics: Not available





PRO BLOCK MMS ECO PART B

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use. May react violently or explode upon contact many organic and inorganic compounds. May ignite if heated strongly and in the presence of an ignition source. Emits toxic fumes when heated.

Conditions to avoid: Do not pierce or burn, even after use. Keep away from incompatible products (see section 7).

Incompatible materials: This product attacks metals.

Hazardous decomposition products: Carbon monoxide and dioxide. Nitrogen oxides.

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE _{product}	4087.72 mg/kg	3618.41 mg/kg	N/A	962.96 mg/l	138.89 mg/l

No	CAS No :	Common name and synonyms	LD ₅₀ oral mg/kg	LD ₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	9046-10-0	Polypropylene glycol diamine	2885	2980	N/A	> 20.00	> 5.00
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	2140	868	N/A	> 20.00	> 5.00
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	1030	> 2000	N/A	> 20.00	> 5.00
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	1160	660	N/A	10.4	1.5
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	1080	1090	N/A	> 20.00	> 5.00

Routes of exposure: This product is absorbed through the respiratory tract, skin and gastrointestinal tract. It is unlikely that the product will be absorbed into the body to any significant extent since it exerts a local action which destroys the tissues.

Symptoms: This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death. The worker may develop skin hypersensitivity as well as allergic or asthma symptoms or breathing difficulties if inhaled.

Delayed and immediate effects: If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness. This product is a respiratory and skin sensitizer. May cause photosensitization. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. High concentration exposure can lead to severe lesions and ulcerations of the esophageal mucosa and gastrointestinal tract. May cause lung, liver and kidney damage. Fever.





PRO BLOCK MMS ECO PART B

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation - Eye irritation	Yes
Skin sensitization	Yes
Respiratory sensitization	Yes
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	N/A
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	N/A
Specific target organ toxicity – repeated exposure	Yes

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	9046-10-0	Polypropylene glycol diamine	Not listed	Not listed	No effects shown.	No effects shown.
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	Not listed	Not listed	The data do not allow for an adequate assessment of mutagenic effects.	Experimental teratogen.
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	Not listed	Not listed	No effects shown.	No effects shown.
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	Not listed	A4	The data do not allow for an adequate assessment of mutagenic effects.	The data do not allow for an adequate evaluation of the effects on reproduction.
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	Not listed	Not listed	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.

Group 2A: probably carcinogenic to humans.

Group 2B: possibly carcinogenic to humans.

Group 3: not classifiable as to its carcinogenicity to humans.

Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.





PRO BLOCK MMS ECO PART B

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	9046-10-0	Polypropylene glycol diamine	10.00 - 30.00	Not available.	Harmful to aquatic life with long lasting effects.	No known adverse effect to the environment.
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	10.00 - 30.00	Not available.	Harmful to aquatic life with long lasting effects.	No known adverse effect to the environment.
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	5.00 - 10.00	Not available.	Harmful to aquatic life with long lasting effects.	No known adverse effect to the environment.
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio- accumulation	Aquatic ecotoxicity
1	9046-10-0	Polypropylene glycol diamine	10.00 - 30.00	No	No	Yes
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	10.00 - 30.00	No	No	No
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	5.00 - 10.00	Yes	No	No
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	0.10 - 1.00	No	No	No
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	0.10 - 1.00	Yes	No	No

Degradability: N/A

Mobility in soil: N/A



PRO BLOCK MMS ECO PART B

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

	TDG	DOT	IMDG	ΙΑΤΑ	
UN Number	2735	2735	2735	2735	
Proper shipping name	AMINES, LIQUID,	AMINES, LIQUID,	AMINES, LIQUID,	AMINES, LIQUID,	
	CORROSIVE, N.O.S.; or	CORROSIVE, N.O.S.; or	CORROSIVE, N.O.S.; or	or CORROSIVE, N.O.S.; or	
	POLYAMINES, LIQUID,	POLYAMINES, LIQUID,	POLYAMINES, LIQUID,	POLYAMINES, LIQUID,	
	CORROSIVE, N.O.S. (N-	CORROSIVE, N.O.S. (N-	CORROSIVE, N.O.S. (N-	CORROSIVE, N.O.S. (N-	
	aminoethylpiperazine)	aminoethylpiperazine)	aminoethylpiperazine)	aminoethylpiperazine)	
Transport hazard class(es)	8	8	8	8	
Packing group		III			

Canada - ERAP

Not applicable

United States - Reportable Quantities (RQ)

No	CAS No :	Common name and synonyms	RQ lbs (kg)
1	107-15-3	Ethylenediamine. 1,2-Diaminoethane	5000 (2270)

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)): N/A

Marine pollutant: Yes

TDG: The identification of marine pollutant is not required for transport by ground.

IMDG: The mark « marine pollutant » is not required when the substance is carried in quantities <= 5L or <= 5 Kg.

Exemption for limited quantity: 5 L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable. In accordance with49 CFR article 172.315 for transportation by a mode other than air, we use the Limited quantities exemption when applicable.

Other exemptions: Not applicable

Special precautions: Not applicable





PRO BLOCK MMS ECO PART B

15. Regulatory information

Canada

No	CAS No :	Common name and synonyms	%	DSL	NDSL	NPRI
1	9046-10-0	Polypropylene glycol diamine	10.00 - 30.00	Х		Х
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	10.00 - 30.00	Х		Х
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	5.00 - 10.00	Х		Х
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	0.10 - 1.00	Х		Х
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	0.10 - 1.00	Х		X

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	9046-10-0	Polypropylene glycol diamine	10.00 - 30.00	Х		
2	140-31-8	N-Aminoethyl piperazine. 2-Piperazine-1-ylethylamine	10.00 - 30.00	Х		Х
3	2855-13-2	Isophorone diamine. 3-Aminoethyl-3,5,5-trimethylcyclohexylamine	5.00 - 10.00	Х		Х
4	107-15-3	Ethylenediamine. 1,2-Diaminoethane	0.10 - 1.00	Х		Х
5	111-40-0	Diethylenetriamine. 2,2'-Iminodi(ethylamine)	0.10 - 1.00	Х		Х

The classification of the product and the SDS were developped in accordance with HPR and HazCom 2012.

16. Other information

Date: 2024/02/28

Version: 1

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.