

# Pro 9750™

## Premium wall base adhesive

Pro 9750 is a premium, solvent-free, stain-free wall base adhesive, with strong wet grab, specially designed for vinyl, rubber and carpet wall base. Pro 9750 is easy to use, easy to clean, resistant to breakdown from plasticizer migration and is formulated with antimicrobial protection to prevent the growth of mold, mildew and bacteria. Pro 9750 is freeze/thaw stable to -12°C.

### Uses

- ◆ For the installation of vinyl, rubber and carpet wall base
- ◆ Use for stair thread installation
- ◆ Solvent free formula for improved indoor air quality
- ◆ Light-colored formula will not stain
- ◆ Strong wet grab and bond strength prevents slip during installation and holds corners tight
- ◆ Antimicrobial protection resists the growth of mold, mildew and bacteria
- ◆ Prevents breakdown of adhesive due to plasticizer migration from vinyl wall base
- ◆ Easy to apply and clean
- ◆ Freeze/thaw stable formula
- ◆ Contributes to LEED® objectives and requirements

### Suitable Substrates

- ◆ Drywall
- ◆ Plaster
- ◆ Masonry, concrete and brick walls
- ◆ Water-based paint residue over porous substrates
- ◆ Wood, such as APA grade plywood

### Packaging

850 mL (28.7 oz) cartridge, 4 L (1.05 US gal) pail, 10 L (2.6 US gal) pail, 15.1 L (4 US gal) pail

### Limitations

- ◆ For interior installations only.
- ◆ Do not use at temperature below 10°C (50°F) or above 35°C (95°F)
- ◆ Do not install over non-porous surfaces, such as vinyl wall coverings, wallpaper, ceramic tiles, metal, non-porous paint or other.
- ◆ Do not use where high moisture and hydrostatic condition and/or recurring moisture problems exist.
- ◆ Do not install over dusty or dirty substrate that could reduce adhesion.
- ◆ Do not store at extreme temperature (hot or cold) and protect from freezing under -12°C (10°F).

### Surface Preparation

Inspect the area to make sure that all surfaces are sound and clean. 24 hours prior to installation, condition the adhesive and lay the wall base flat at normal room temperature.



### Mixing

No mixing is required. This product is ready to use as is.



### Application

1. Prepare the wall base according to the manufacturer's instructions to fit the internal and external corners. You may require a marker, a knife and a hand groover for this step.
2. Apply the adhesive directly on the wall base with a 1/8" v-notched trowel or an appropriate 2, 3 or 5 holes nozzle applicator by making zigzag (the nozzle method may require a trowel pass to spread evenly and prevent normal drying marks from appearing by telegraphy once the adhesive is dried).
3. There is no need to let it flash so it can be installed right away.
4. Press the base firmly in place and roll the entire surface with a hand roller toward your starting point to prevent stretching and joint opening of the base. Also, the rolling should be done from the top down to push any excess adhesive toward the bottom of the base to prevent any overflow of adhesive at the top.

### Clean-up

Wet adhesive can easily be removed with a clean rag and warm soapy water. Dried adhesive can be removed using mineral spirits; however caution should be taken in order to avoid discoloration or other harmful effect on the base material.



# Pro 9750™ continued

**Technical Data** for Pro 9750 (@ 23°C [73°F] and 50% RH)

**Open time:** ..... Up to 20 minutes  
**Drying time:** ..... 24-48 hours  
**Specific gravity:** ..... 10.8 - 11.6 lbs/gal (1.30- 1.40 kg/L)  
**pH:** ..... 8-10  
**Consistency:** ..... Smooth and easy to spread  
**VOC content (per Rule # 1168 of California's SCAQMD):** ..... 41 g/L  
**Odor:** ..... Very low  
**Freeze thaw stability:** ..... Pass 5 cycles at -12°C (10°F)  
**Solid content:** ..... 50-65%

**Approximate coverage**

	Coverage per linear ft (linear m)		
	2.5" (6.4 cm) wall base	4" (10.2 cm) wall base	6" (15.2 cm) wall base
1/8" x 1/8" x 1/8" (3 x 3 x 3 mm) V-notched trowel			
2.8.7 oz (849 mL)	70-95 (21-29)	40-60 (12-18)	30-40 (9-12)
1 U.S. gal (3.79 L)	310-405 (94-123)	190-250 (58-76)	130-170 (40-52)
2.6 U.S. gal (10 L)	790-985 (240-300)	490-610 (150-185)	330-410 (100-125)
4 U.S. gal (15.1 L)	1290-1515 (393-462)	800-940 (244-287)	540-635 (165-194)



**Shelf life**

12 months if kept in its original unopened packaging and stored in a dry location.  
 Protect from freezing under -12°C (5°F)

**Health and Safety**

Refer to the Material Safety Data Sheet (MSDS) for complete details.

## Warranty

Prima warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. Prima's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

## Contact Information

**PROMA Adhesives Inc.**

9801, Parkway, Anjou, Quebec Canada H1J 1P3  
 Tel.: 514.852.8585  
 Fax: 514.852.8225  
 Toll-free: 1 866.51.PROMA (77662)  
 Email: info@prima.ca

